

EXECUTIVE / CONSTRUCTION PRO SERIES:				
Glass Package	Winter U-Factor	SHGC	Visible Transmission	AAMA Rating
	(Insulating Performance)	(Solar Performance)	(Daylight)	
Window Configuration	SH / SL / PW	SH / SL / PW	SH / SL / PW	SH / SL / PW
Dual Glaze: Low E / Clear Insulated - Argon	0.29 / 0.28 / 0.26	0.28 / 0.28 / 0.30	54% / 53% / 57%	H-R50 / HS-R35 / F-R35
ABOVE RATINGS ARE COMPARITIVE NUMBERS ONLY. THEY ARE CERTIFIED NFRC / AAMA RATINGS BASED UPON STANDARD FEATURES OF EACH WINDOW SYSTEM. CHOICE OF GRIDS AND OTHER OPTIONS WILL EFFECT TRUE VALUES.				

PRESIDENTIAL / ENERGY MASTER SERIES:				
Glass Package	Winter U-Factor	SHGC	Visible Transmission	AAMA Rating
	(Insulating Performance)	(Solar Performance)	(Daylight)	
Window Configuration	DH / SH / SL / PW	DH / SH / SL / PW	DH / SH / SL / PW	DH / SH / SL / PW
Dual Glaze: Low E / Clear Insulated - Argon	0.30 / 0.29 / 0.29 / 0.27	0.27 / 0.28 / 0.28 / 0.29	51% / 53% / 53% / 56%	H-R40 / H-R50 / HS-R35 / F-R36
ABOVE RATINGS ARE COMPARITIVE NUMBERS ONLY. THEY ARE CERTIFIED NFRC / AAMA RATINGS BASED UPON STANDARD FEATURES OF EACH WINDOW SYSTEM. CHOICE OF GRIDS AND OTHER OPTIONS WILL EFFECT TRUE VALUES.				

TWINSULATOR SERIES:				
Glass Package	Winter U-Factor	SHGC	Visible Transmission	AAMA Rating
	(Insulating Performance)	(Solar Performance)	(Daylight)	
Window Configuration	DH / SH / SL / PW	DH / SH / SL / PW	DH / SH / SL / PW	DH / SH / SL / PW
Dual Glaze: Low E / Clear Insulated - Argon	0.43 / 0.46 / 0.48 / 0.38	0.34 / 0.32 / 0.32 / 0.34	55% / 55% / 55% / 62%	H-C30 : H-C50* / H-C35 / NFRC-100 / F-C41
* Double Hung Rating: H-C30 54" x 90" / H-C50 48" x 72"				
ABOVE RATINGS ARE COMPARITIVE NUMBERS ONLY. THEY ARE CERTIFIED NFRC / AAMA RATINGS BASED UPON STANDARD FEATURES OF EACH WINDOW SYSTEM. CHOICE OF GRIDS AND OTHER OPTIONS WILL EFFECT TRUE VALUES.				

BUILDERS REPLACEMENT SERIES:				
Glass Package	Winter U-Factor	SHGC	Visible Transmission	AAMA Rating
	(Insulating Performance)	(Solar Performance)	(Daylight)	
Window Configuration	SH / SL / PW	SH / SL / PW	SH / SL / PW	SH / SL / PW
Dual Glaze: Low E / Clear Insulated - Argon	0.61 / NA / 0.49	0.36 / NA / 0.36	58% / NA / 61%	NA / NA / F-C41
ABOVE RATINGS ARE COMPARITIVE NUMBERS ONLY. THEY ARE CERTIFIED NFRC / AAMA RATINGS BASED UPON STANDARD FEATURES OF EACH WINDOW SYSTEM. CHOICE OF GRIDS AND OTHER OPTIONS WILL EFFECT TRUE VALUES.				

RATINGS ARE CURRENTLY BEING RE-TESTED FOR CERTIFICATION.