



Quick-Tilt® CONSTANT FORCE SYSTEM

Quick-Tilt® is quiet, corrosion-resistant and comes preassembled to easily install in residential, tilt-window applications. For quick assembly, it was designed for the pivot bar to easily drop-in and tie-in to the carrier. Its alternating coil design prevents cantilevering or twisting of the carrier that can diminish locking performance. Quick-Tilt® remains hidden during normal sash operation, requires no adjustment and, of course, performs reliably. It is rated Class 2 on the American Architectural Manufacturers Association (AAMA) Verified Components List.

COVER (OPTIONAL)
Encloses spring assembly.
Minimizes contamination
by debris.

BUMPER (OPTIONAL)
Used in place of a stop.
Prevents carrier from
colliding with spring
assembly.

TAMPERLOK (RECOMMENDED)
This safety feature, when snapped
into the carrier, prevents the homeowner
from accidentally detaching the sash.

TIE-IN PIVOT BAR
When seated in the carrier, it secures
the sash to the frame, preventing the
sash from accidentally detaching or
falling out.

**PREASSEMBLED STAINLESS
STEEL SPRINGS**
Greaseless, corrosion-resistant
springs uncoil against each other
in opposite directions to minimize
friction and maximize smooth,
silent operation.

DIE CAST METAL CAM
For strength and durability.

